


## Product Category Part Description

H814-16-12-16-M Tube to Female Pipe Thread Run Tee Assembly



## **DIMENSIONS**

| A     | 1.000     |
|-------|-----------|
| A"    | 1.000     |
| B-NPT | 3/4" - 14 |
| C-HEX | 1.63      |
| D     | 0.500     |
| D"    | 0.500     |
| E     | 2.75      |
| F     | 1.94      |

## **GENERAL**

| Pressure Rating      | 6000 PSI   |
|----------------------|--|
| Tailpiece Material   | Monel®, ASTM B164, UNS N04405                      |
| Threadpiece Material | Monel®, ASTM B564, UNS N04400                      |
| O-Ring Material      | Viton® Fluorocarbon Type 1, Class 2 (90 durometer) |
| Connection 1 Type    | Female Tube Socket                                 |

## cpvmfg.com | 484.731.4010

Connection 3 Type

Female Tube Socket

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting a size, the total system design must be considered to ensure safe, trouble-free performance. Furction, 6) material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.