
Product Category Product Line Part Description 12D-G-B-R Cast Iron & Bronze Flanged Check Valves (10D, 11D, 12D, 13D, 20D, 21D) CLASS 150 Flange Style Silent Check Valve with Bronze Body and Bronze Trim



## **DIMENSIONS**

| Face to Face        | 8     |
|---------------------|-------|
| Dia. of Bolt Circle | 11.75 |
| Dia. of Flange      | 13.50 |
| No. of Studs        | 8     |
| Dia. of Studs       | 0.75  |
| Length of Studs     | 12.50 |
| Weight (lbs.)       | 110   |

## **GENERAL**

| Pressure Rating     | up to 290 PSI                      |
|---------------------|------------------------------------|
| Temperature Range   | -30°F to 250°F (-34°C to 121°C)    |
| Standard Soft Goods | Buna-N O-Rings                     |
| Cartridge Type      | Check                              |
| Connection Type     | ANSI B16.5 Flange                  |
| Connection Size     | 8"                                 |
| Body Material       | Valve Bronze, ASTM B61, UNS C92200 |

## **OPTIONS**

| Dort 9 Vant Ontions | [ DD] Droin Dlug Above Cost (2/4" NDT) |
|---------------------|--|
| Port & Vent Options | [-DP] Drain Plug Above Seat (3/4" NPT) |

cpvmfg.com | 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.