



**Product Category**

113D-E-SS-R

**Product Line**

Steel Flanged Check Valves (110D, 111D, 113D, 114D, 115D)

**Part Description**

CLASS 600 Flange Style Silent Check Valve with Steel Body and Stainless Steel Trim



## DIMENSIONS

|                     |       |
|---------------------|-------|
| Face to Face        | 4.63  |
| Dia. of Bolt Circle | 10.50 |
| Dia. of Flange      | 13.00 |
| No. of Studs        | 8     |
| Dia. of Studs       | 1.00  |
| Length of Studs     | 12.50 |
| Weight (lbs.)       | 50    |

## GENERAL

|                     |                                          |
|---------------------|------------------------------------------|
| Pressure Rating     | up to 1500 PSI                           |
| Temperature Range   | -30°F to 250°F (-34°C to 121°C)          |
| Standard Soft Goods | Buna-N O-Rings                           |
| Cartridge Type      | Check                                    |
| Connection Type     | ANSI B16.5 Flange                        |
| Connection Size     | 5"                                       |
| Body Material       | Carbon Steel, ASTM A216, WCB, UNS J03002 |

## OPTIONS

|                     |                                        |
|---------------------|----------------------------------------|
| Port & Vent Options | [-DP] Drain Plug Above Seat (3/4" NPT) |
|---------------------|----------------------------------------|

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.