

**Product Category** 


Product Line

Part Description

113D-F-B-R

Steel Flanged Check Valves (110D, 111D, 113D, 114D, 115D)

CLASS 600 Flange Style Silent Check Valve with Steel Body and Bronze Trim



## DIMENSIONS

Face to Face	5.5
Dia. of Bolt Circle	11.50
Dia. of Flange	14.00
No. of Studs	12
Dia. of Studs	1.00
Length of Studs	14.00
Weight (Ibs.)	74

## **GENERAL**

Pressure Rating	up to 1500 PSI
Temperature Range	-30°F to 250°F (-34°C to 121°C)
Standard Soft Goods	Buna-N O-Rings
Cartridge Type	Check
Connection Type	ANSI B16.5 Flange
Connection Size	6"
Body Material	Carbon Steel, ASTM A216, WCB, UNS J03002

## https://www.cpvmfg.com 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the totabystem design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.



## **OPTIONS**

**Port & Vent Options** 

**Optional Soft Goods** 

[-DP] Drain Plug Above Seat (3/4" NPT)

Viton® O-Rings, EPDM O-Rings

https://www.cpvmfg.com 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the totabystem design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.