

115D-A-B-R 07/08/2025 8:36 AM


Product Category

Product Line

Part Description

115D-A-B-R Steel Flanged Check Valves (110D, 111D, 113D, 114D, 115D)

CLASS 1500 Flange Style Silent Check Valve with Steel Body and Bronze Trim



DIMENSIONS

Face to Face	2.63
Dia. of Bolt Circle	6.50
Dia. of Flange	8.50
No. of Studs	8
Dia. of Studs	0.88
Length of Studs	10.50
Weight (Ibs.)	16

GENERAL

Pressure Rating	1500 PSI
Temperature Range	-30°F to 250°F (-34°C to 121°C)
Standard Soft Goods	Buna-N O-Rings
Cartridge Type	Check
Connection Type	ANSI B16.5 Flange
Connection Size	2"
Body Material	Carbon Steel, ASTM A216, WCB, UNS J03002

https://www.cpvmfg.com 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the totabystem design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.



OPTIONS

Port & Vent Options

Optional Soft Goods

[-DP] Drain Plug Above Seat (3/8" NPT)

Viton® O-Rings, EPDM O-Rings

https://www.cpvmfg.com 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the totabystem design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.