

# DATA SHEET

115D-E-SS-R 07/11/2025 10:00 PM

**Product Category** 


Product Line

Part Description

115D-E-SS-R

Steel Flanged Check Valves (110D, 111D, 113D, 114D, 115D)

CLASS 1500 Flange Style Silent Check Valve with Steel Body and Stainless Steel Trim



# DIMENSIONS

Face to Face	4.63
Dia. of Bolt Circle	11.50
Dia. of Flange	14.75
No. of Studs	8
Dia. of Studs	1.50
Length of Studs	16.00
Weight (Ibs.)	83

# **GENERAL**

Pressure Rating	up to 3750 PSI
Temperature Range	-30°F to 250°F (-34°C to 121°C)
Standard Soft Goods	Buna-N O-Rings
Cartridge Type	Check
Connection Type	ANSI B16.5 Flange
Connection Size	5"
Body Material	Carbon Steel, ASTM A216, WCB, UNS J03002

#### https://www.cpvmfg.com 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the totabystem design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.



#### **OPTIONS**

**Port & Vent Options** 

**Optional Soft Goods** 

[-DP] Drain Plug Above Seat (3/4" NPT)

Viton® O-Rings, EPDM O-Rings

https://www.cpvmfg.com 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the totabystem design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.