


DATA SHEET

12D-D-SS-R 07/14/2025 7:52 PM

Product Category

Product Line Part Description 12D-D-SS-R

Cast Iron & Bronze Flanged Check Valves (10D, 11D, 12D, 13D, 20D, 21D) CLASS 150 Flange Style Silent Check Valve with Bronze Body and Stainless Steel Trim



DIMENSIONS

Face to Face	4
Dia. of Bolt Circle	7.50
Dia. of Flange	9.00
No. of Studs	8
Dia. of Studs	0.63
Length of Studs	8.50
Weight (Ibs.)	28

GENERAL

Pressure Rating	up to 290 PSI
Temperature Range	-30°F to 250°F (-34°C to 121°C)
Standard Soft Goods	Buna-N O-Rings
Cartridge Type	Check
Connection Type	ANSI B16.5 Flange
Connection Size	4"
Body Material	Valve Bronze, ASTM B61, UNS C92200

https://www.cpvmfg.com 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the totabystem design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.



OPTIONS

Port & Vent Options

Optional Soft Goods

[-DP] Drain Plug Above Seat (1/2" NPT)

Viton® O-Rings, EPDM O-Rings

https://www.cpvmfg.com 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the totabystem design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.