


Product Category
Product Line
Part Description

1380-0-NC FloMaster® Actuated O-SEAL® Shutoff Valve (1300 Series)
1/8" Globe Shutoff Actuated Valve, O-SEAL® Ends, Normally Closed



## **DIMENSIONS**

Port Dia.	0.22
A	2.750
CRN	0C17716.2
D-THREAD	1.000"-14UNS
E	4.00
F (Normally Closed)	11.5

https://www.cpvmfg.com 484.731.4010



## **GENERAL**

Pressure Rating	6000 PSI
Temperature Range	-15°F to 400°F (-26°C to 204°C)
Standard Soft Goods	[-G] Polyurethane® Packing and Viton® O-Rings
Cartridge Type	Shutoff
Connection Type	O-SEAL® Union Thread
Connection Size	1/8"
Body Material	Nickel Aluminum Bronze, ASTM B148, UNS C95800
Bonnet Material	Nickel Aluminum Bronze, ASTM B150, UNS C63200
CRN	0C17716.2

## **OPTIONS**

[-VC] Vacuum Service	Option to add additional softgoods for internal vacuum service.
Port & Vent Options	[-PA] Port Above Seat (1/8" NPT), [-PB] Port Below Seat (1/8" NPT), '[-VA] Vent Above Seat (3/8"-24 SAE), [-VB] Vent Below Seat (3/8"-24 SAE),
Optional Soft Goods	[-B] Polyurethane® Packing and Buna-N O-Rings, [-C] Viton® Packing & O-Rings, [-D] EPDM Packing & O-Rings

https://www.cpvmfg.com 484.731.4010