

DATA SHEET 14D-D-B-R

14D-D-B-R

14D-D-B-R 07/16/2025 7:45 PM


Product Category

Product Line

Part Description

Air Check Valves (14D, 15D, 16D, 17D, 125D, 126D)

CLASS 125 Flange Style Silent Air Check Valve with Cast Iron Body and Bronze Trim



DIMENSIONS

Face to Face	4
Dia. of Bolt Circle	7.50
Dia. of Flange	9.00
No. of Studs	8
Dia. of Studs	0.63
Length of Studs	8.50
Weight (lbs.)	24

GENERAL

Pressure Rating	up to 200 PSI
Temperature Range	-30°F to 250°F (-34°C to 121°C)
Standard Soft Goods	Buna-N O-Rings
Cartridge Type	Air Check
Connection Type	ANSI B16.5 Flange
Connection Size	4"
Body Material	Cast Iron, ASTM A126, CL. B

https://www.cpvmfg.com 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the totabystem design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.



OPTIONS

Port & Vent Options

Optional Soft Goods

[-DP] Drain Plug Above Seat (1/2" NPT)

Viton® O-Rings, EPDM O-Rings

https://www.cpvmfg.com 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the totabystem design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.