



Product Category

14D-G-B-R

Product Line

Air Check Valves (14D, 15D, 16D, 17D, 125D, 126D)

Part Description

CLASS 125 Flange Style Silent Air Check Valve with Cast Iron Body and Bronze Trim



## DIMENSIONS

|                     |       |
|---------------------|-------|
| Face to Face        | 8     |
| Dia. of Bolt Circle | 11.75 |
| Dia. of Flange      | 13.50 |
| No. of Studs        | 8     |
| Dia. of Studs       | 0.75  |
| Length of Studs     | 12.50 |
| Weight (lbs.)       | 100   |

## GENERAL

|                     |                                 |
|---------------------|---------------------------------|
| Pressure Rating     | up to 200 PSI                   |
| Temperature Range   | -30°F to 250°F (-34°C to 121°C) |
| Standard Soft Goods | Buna-N O-Rings                  |
| Cartridge Type      | Air Check                       |
| Connection Type     | ANSI B16.5 Flange               |
| Connection Size     | 8"                              |
| Body Material       | Cast Iron, ASTM A126, CL. B     |



OPTIONS

|                     |  |
|---------------------|--|
| Port & Vent Options | [-DP] Drain Plug Above Seat (3/4" NPT) |
| Optional Soft Goods | Viton® O-Rings, EPDM O-Rings           |