



Product

14D-G-SS-R


Category

Product Line

Air Check Valves (14D, 15D, 16D, 17D, 125D, 126D)

Part Description

CLASS 125 Flange Style Silent Air Check Valve with Cast Iron Body and Stainless Steel Trim



DIMENSIONS

Face to Face	8
Dia. of Bolt Circle	11.75
Dia. of Flange	13.50
No. of Studs	8
Dia. of Studs	0.75
Length of Studs	12.50
Weight (lbs.)	100

GENERAL

Pressure Rating	up to 200 PSI
Temperature Range	-30°F to 250°F (-34°C to 121°C)
Standard Soft Goods	Buna-N O-Rings
Cartridge Type	Air Check
Connection Type	ANSI B16.5 Flange
Connection Size	8"

Body Material	Cast Iron, ASTM A126, CL. B
---------------	-----------------------------

OPTIONS

Port & Vent Options	[-DP] Drain Plug Above Seat (3/4" NPT)
Optional Soft Goods	Viton® O-Rings, EPDM O-Rings

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.