

DATA SHEET 151-5

09/15/2025 11:28 PM


Product Category

Product Line

Part Description

151-5

NPT Threaded Relief Valves (150 Series) Steel Angle Relief Valve with Female Pipe Thread (NPT) Ends



DIMENSIONS

Overall Length	7
Female Inlet and Outlet (NPT)	1.000"-11.5
Center of Outlet to Bottom	2
Weight (Ibs.)	5.3

https://www.cpvmfg.com 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the totabystem design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.



GENERAL

Pressure Rating	300 PSI
Temperature Range	-30°F to 250°F (-34°C to 121°C)
Standard Soft Goods	Buna-N O-Rings
Cartridge Type	Relief
Connection Type	Female Pipe Thread (NPT)
Connection Size	1.00"
Body Material	Carbon Steel, ASTM A36/A311, UNS K02600/G10180
Bonnet Material	Carbon Steel, ASTM A36/A311, UNS K02600/G10180

OPTIONS

Optional Soft Goods

Viton® O-Rings, EPDM O-Rings

https://www.cpvmfg.com 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the totabystem design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.