

Product Category


15D-D-SS-R

Product Line

Air Check Valves (14D, 15D, 16D, 17D, 125D, 126D)

Part Description

CLASS 250 Flange Style Silent Air Check Valve with Cast Iron Body and Stainless Steel Trim



DIMENSIONS

| Face to Face | 4 |
|---------------------|-------|
| Dia. of Bolt Circle | 7.88 |
| Dia. of Flange | 10.00 |
| No. of Studs | 8 |
| Dia. of Studs | 0.75 |
| Length of Studs | 9.50 |
| Weight (lbs.) | 24 |

GENERAL

| Pressure Rating | up to 500 PSI |
|---------------------|---------------------------------|
| Temperature Range | -30°F to 250°F (-34°C to 121°C) |
| Standard Soft Goods | Buna-N O-Rings |
| Cartridge Type | Air Check |
| Connection Type | ANSI B16.5 Flange |
| Connection Size | 4" |
| Body Material | Cast Iron, ASTM A126, CL. B |

https://www.cpvmfg.com 484.731.4010

15D-D-SS-R 07/12/2025 11:06 PM

OPTIONS

| Port & Vent Options | [-DP] Drain Plug Above Seat (1/2" NPT) |
|---------------------|--|
| Optional Soft Goods | Viton® O-Rings, EPDM O-Rings |

https://www.cpvmfg.com 484.731.4010