

DATA SHEET

16D-D-SS-R

16D-D-SS-R 09/16/2025 6:35 PM


Air Check Valves (14D, 15D, 16D, 17D, 125D, 126D)

Product Category

Product Line

Part Description

CLASS 150 Flange Style Silent Air Check Valve with Bronze Body and Stainless Steel Trim



DIMENSIONS

Face to Face	4
Dia. of Bolt Circle	7.50
Dia. of Flange	9.00
No. of Studs	8
Dia. of Studs	0.63
Length of Studs	8.50
Weight (Ibs.)	28

GENERAL

Pressure Rating	up to 290 PSI
Temperature Range	-30°F to 250°F (-34°C to 121°C)
Standard Soft Goods	Buna-N O-Rings
Cartridge Type	Air Check
Connection Type	ANSI B16.5 Flange
Connection Size	4"
Body Material	Valve Bronze, ASTM B61, UNS C92200

https://www.cpvmfg.com 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the totabystem design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.



OPTIONS

Port & Vent Options

Optional Soft Goods

[-DP] Drain Plug Above Seat (1/2" NPT)

Viton® O-Rings, EPDM O-Rings

https://www.cpvmfg.com 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the totabystem design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.