

09/17/2025 3:54 AM

Product Category


Product Line

Part Description

17D-D-B-R

Air Check Valves (14D, 15D, 16D, 17D, 125D, 126D)

CLASS 300 Flange Style Silent Air Check Valve with Bronze Body and Bronze Trim



DIMENSIONS

| Face to Face | 4 |
|---------------------|-------|
| Dia. of Bolt Circle | 7.88 |
| Dia. of Flange | 10.00 |
| No. of Studs | 8 |
| Dia. of Studs | 0.75 |
| Length of Studs | 9.50 |
| Weight (Ibs.) | 24 |

GENERAL

| Pressure Rating | up to 750 PSI |
|---------------------|------------------------------------|
| Temperature Range | -30°F to 250°F (-34°C to 121°C) |
| Standard Soft Goods | Buna-N O-Rings |
| Cartridge Type | Air Check |
| Connection Type | ANSI B16.5 Flange |
| Connection Size | 4" |
| Body Material | Valve Bronze, ASTM B61, UNS C92200 |

https://www.cpvmfg.com 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the totabystem design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.



OPTIONS

Port & Vent Options

Optional Soft Goods

[-DP] Drain Plug Above Seat (1/2" NPT)

Viton® O-Rings, EPDM O-Rings

https://www.cpvmfg.com 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the totabystem design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.