



Product Category


380-5

Product Line

O-SEAL® Shutoff Valves (300 Series)

Part Description

1.00" Globe Shutoff Valve with O-SEAL® Ends



DIMENSIONS

| | |
|-----------|--------------|
| Port Dia. | 0.81 |
| A | 5.250 |
| B | 7.63 |
| CRN | 0C17716.2 |
| E | 7.25 |
| F-THREAD | 2.313"-12UNS |
| Lift | 0.59 |



GENERAL

| | |
|----------------------------|---|
| Pressure Rating | 6000 PSI |
| Temperature Range | -15°F to 275°F (-26°C to 135°C) |
| Standard Soft Goods | [-G] Polyurethane® Packing and Viton® O-Rings |
| Cartridge Type | Shutoff |
| Connection Type | O-SEAL® Union Thread |
| Connection Size | 1.00" |
| Body Material | Nickel Aluminum Bronze, ASTM B148, UNS C95800 |
| Bonnet Material | Nickel Aluminum Bronze, ASTM B148/B150, UNS C95800/C63200 |
| CRN | OC17716.2 |

OPTIONS

| | |
|--------------------------------|---|
| [-VC] Vacuum Service | Option to add additional softgoods for internal vacuum service. |
| [-P] Panel Mount | Option to add external thread and panel mounting nut to bonnet |
| Port & Vent Options | [-PA] Port Above Seat (1/4" NPT), [-PB] Port Below Seat (1/4" NPT), [-VA] Vent Above Seat (1/2"-13 SAE), [-VB] Vent Below Seat (1/2"-13 SAE), |
| Optional Soft Goods | [-B] Polyurethane® Packing and Buna-N O-Rings, [-C] Viton® Packing & O-Rings, [-D] EPDM Packing & O-Rings |