

**Product Category** 


**Part Description** 

**Product Line** 

580-6

O-SEAL® Stop-Check Valves (500 Series)

1.25" Globe Stop-Check Valve with O-SEAL® Ends



## **DIMENSIONS**

Port Dia.	1
A	6.500
В	7.63
CRN	OC17716.2
E	9.00
F-THREAD	2.750"-12UN
Lift	0.59



## **GENERAL**

Pressure Rating	6000 PSI
Temperature Range	-15°F to 275°F (-26°C to 135°C)
Standard Soft Goods	[-G] Polyurethane® Packing and Viton® O-Rings
Cartridge Type	Stop-Check
Connection Type	O-SEAL® Union Thread
Connection Size	1.25"
Body Material	Nickel Aluminum Bronze, ASTM B148, UNS C95800
Bonnet Material	Nickel Aluminum Bronze, ASTM B148, UNS C95800
CRN	0C17716.2

## **OPTIONS**

[-VC] Vacuum Service	Option to add additional softgoods for internal vacuum service.
[-P] Panel Mount	Option to add external thread and panel mounting nut to bonnet
Port & Vent Options	[-PA] Port Above Seat (1/4" NPT), [-PB] Port Below Seat (1/4" NPT), '[-VA] Vent Above Seat (1/2"-13 SAE), [-VB] Vent Below Seat (1/2"-13 SAE),
Optional Soft Goods	[-B] Polyurethane® Packing and Buna-N O-Rings, [-C] Viton® Packing & O-Rings, [-D] EPDM Packing & O-Rings

https://www.cpvmfg.com 484.731.4010