
Product Category Product Line Part Description 670-2 O-SEAL® Check Valves (600 Series) 3/8" Globe Check Valve with Welded Ends



DIMENSIONS

| Port Dia. | 0.44 |
|-----------------------------|------|
| A | |
| В | |
| D | |
| F (Pipe Size) | |
| F (Pipe Size) F (Tube Size) | |

GENERAL

| Pressure Rating | 6000 PSI |
|---------------------|---|
| Temperature Range | -15°F to 275°F (-26°C to 135°C) |
| Standard Soft Goods | [-C] Viton® O-Rings |
| Cartridge Type | Check |
| Connection Type | Socketweld |
| Connection Size | 3/8" |
| Body Material | 316/L Stainless Steel, ASTM A276, UNS S31603 |
| Bonnet Material | Nickel Aluminum Bronze, ASTM B150, UNS C63200 |

OPTIONS

| Port & Vent | [-PA] Port Above Seat (1/8" NPT), [-PB] Port Below Seat (1/8" NPT), '[-VA] Vent Above |
|---------------|---|
| Options | Seat (3/8"-24 SAE), [-VB] Vent Below Seat (3/8"-24 SAE), |
| Optional Soft | [-B] Polyurethane® Packing and Buna-N O-Rings, [-C] Viton® Packing & O-Rings, [-D] |