
Product Category
Product Line
Part Description

681-7
O-SEAL® Check Valves (600 Series)
1.50" Angle Check Valve with O-SEAL® Ends



## **DIMENSIONS**

| Port Dia. | 1.25         |
|-----------|--------------|
| A         | 4.000        |
| В         | 6.00         |
| С         | 4.00         |
| C-THREAD  | 3.063"-12UNS |

## **GENERAL**

| Pressure Rating     | 6000 PSI                                      |
|---------------------|---|
| Temperature Range   | -15°F to 275°F (-26°C to 135°C)               |
| Standard Soft Goods | [-C] Viton® O-Rings                           |
| Cartridge Type      | Check   |
| Connection Type     | O-SEAL® Union Thread                          |
| Connection Size     | 1.50"   |
| Body Material       | Nickel Aluminum Bronze, ASTM B148, UNS C95800 |
| Bonnet Material     | Nickel Aluminum Bronze, ASTM B148, UNS C95800 |

https://www.cpvmfg.com 484.731.4010



## **OPTIONS**

| Port & Vent Options | [-PA] Port Above Seat (1/4" NPT), [-PB] Port Below Seat (1/4" NPT), '[-VA] Vent Above Seat (1/2"-13 SAE), [-VB] Vent Below Seat (1/2"-13 SAE), |
|---------------------|--|
| Optional Soft Goods | [-B] Polyurethane® Packing and Buna-N O-Rings, [-C] Viton® Packing & O-Rings, [-D] EPDM Packing & O-Rings                                      |