




**Product Category**

**Product Line**

**Part Description**

G0SGPF-04-NC

FloMaster® Actuated G-Series® Shutoff Valves (G-S Series)  
Globe Shutoff Actuated Valve, Female NPT Ends, Normally Closed



## DIMENSIONS

|                     |         |
|---------------------|---------|
| Orifice             | 0.218   |
| A-NPT :             | 1/4"-18 |
| B                   | 2.38    |
| E                   | 4.00    |
| F (Normally Open)   | 6.19    |
| F (Normally Closed) | 10.63   |

## GENERAL

|                     |                                               |
|---------------------|-----------------------------------------------|
| Pressure Rating     | 6000 PSI                                      |
| Temperature Range   | -15°F to 400°F (-26°C to 204°C)               |
| Standard Soft Goods | [-G] Polyurethane® Packing and Viton® O-Rings |
| Cartridge Type      | Shutoff                                       |
| Connection Type     | Female Pipe Thread (NPT)                      |

|                        |                                              |
|------------------------|----------------------------------------------|
| <b>Connection Size</b> | 1/4"                                         |
| <b>Body Material</b>   | 316/L Stainless Steel, ASTM A182, UNS S31603 |
| <b>Bonnet Material</b> | 316/L Stainless Steel, ASTM A276, UNS S31603 |

## OPTIONS

|                             |                                                                                                           |
|-----------------------------|-----------------------------------------------------------------------------------------------------------|
| <b>[-VC] Vacuum Service</b> | Option to add additional softgoods for internal vacuum service.                                           |
| <b>Optional Soft Goods</b>  | [-B] Polyurethane® Packing and Buna-N O-Rings, [-C] Viton® Packing & O-Rings, [-D] EPDM Packing & O-Rings |

cpvmfg.com | 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.