

Product Category

G1SGPF-06-NC

Product Line

FloMaster® Actuated G-Series® Shutoff Valves (G-S Series)

Part Description

Globe Shutoff Actuated Valve, Female NPT Ends, Normally Closed



## DIMENSIONS

|                     |         |
|---------------------|---------|
| Orifice             | 0.313   |
| A-NPT :             | 3/8"-18 |
| B                   | 2.88    |
| E                   | 4.00    |
| F (Normally Open)   | 9.85    |
| F (Normally Closed) | 13.25   |



## GENERAL

|                            |   |
|----------------------------|---|
| <b>Pressure Rating</b>     | 6000 PSI                                      |
| <b>Temperature Range</b>   | -15°F to 400°F (-26°C to 204°C)               |
| <b>Standard Soft Goods</b> | [-G] Polyurethane® Packing and Viton® O-Rings |
| <b>Cartridge Type</b>      | Shutoff                                       |
| <b>Connection Type</b>     | Female Pipe Thread (NPT)                      |
| <b>Connection Size</b>     | 3/8"  |
| <b>Body Material</b>       | 316/L Stainless Steel, ASTM A182, UNS S31603  |
| <b>Bonnet Material</b>     | 316/L Stainless Steel, ASTM A276, UNS S31603  |

## OPTIONS

|                             |   |
|-----------------------------|---|
| <b>[-VC] Vacuum Service</b> | Option to add additional softgoods for internal vacuum service.   |
| <b>Optional Soft Goods</b>  | [-B] Polyurethane® Packing and Buna-N O-Rings, [-C] Viton® Packing & O-Rings, [-D] EPDM Packing & O-Rings |