
G1SGPF-06-NO 11/06/2025 3:28 PM

Product Category
Product Line
Part Description

G1SGPF-06-NO FloMaster® Actuated G-Series® Shutoff Valves (G-S Series)

Globe Shutoff Actuated Valve, Female NPT Ends, Normally Open



DIMENSIONS

Orifice	0.313
A-NPT:	3/8"-18
В	2.88
E	4.00
F (Normally Open)	9.85
F (Normally Closed)	13.25

https://www.cpvmfg.com 484.731.4010

DATA SHEET

G1SGPF-06-NO 11/06/2025 3:28 PM

GENERAL

Pressure Rating	6000 PSI
Temperature Range	-15°F to 400°F (-26°C to 204°C)
Standard Soft Goods	[-G] Polyurethane® Packing and Viton® O-Rings
Cartridge Type	Shutoff
Connection Type	Female Pipe Thread (NPT)
Connection Size	3/8"
Body Material	316/L Stainless Steel, ASTM A182, UNS S31603
Bonnet Material	316/L Stainless Steel, ASTM A276, UNS S31603

OPTIONS

[-VC] Vacuum Service	Option to add additional softgoods for internal vacuum service.
Optional Soft Goods	[-B] Polyurethane® Packing and Buna-N O-Rings, [-C] Viton® Packing & O-Rings, [-D] EPDM Packing & O-Rings

https://www.cpvmfg.com 484.731.4010