


Product Category G2CGPF-08

Product Line G-Series® Check Valves (G-C Series)

Part Description Globe Check Valve with Female Pipe Thread (NPT) Ends



DIMENSIONS

| Orifice | 0.438 |
|---------|---------|
| A-NPT: | 1/2"-14 |
| В | 3.38 |
| н | 2.66 |

GENERAL

| Pressure Rating | 6000 PSI |
|---------------------|---|
| Temperature Range | -15°F to 400°F (-26°C to 204°C) |
| Standard Soft Goods | [-G] Polyurethane® Packing and Viton® O-Rings |
| Cartridge Type | Check |
| Connection Type | Female Pipe Thread (NPT) |
| Connection Size | 1/2" |
| Body Material | 316/L Stainless Steel, ASTM A182, UNS S31603 |
| Bonnet Material | 316/L Stainless Steel, ASTM A276, UNS S31603 |

https://www.cpvmfg.com 484.731.4010

OPTIONS

| [-VC] Vacuum Service | Option to add additional softgoods for internal vacuum service. |
|----------------------|---|
| Optional Soft Goods | [-B] Polyurethane® Packing and Buna-N O-Rings, [-C] Viton® Packing & O-Rings, [-D] EPDM Packing & O-Rings |

https://www.cpvmfg.com 484.731.4010