



**Product Category** G2SGPS-06-NC  
**Product Line** FloMaster® Actuated G-Series® Shutoff Valves (G-S Series)  
**Part Description** Globe Shutoff Actuated Valve, Socketweld Pipe Ends, Normally Closed

## DIMENSIONS

|                     |       |
|---------------------|-------|
| Orifice             | 0.438 |
| A (NPS)             | 0.675 |
| B                   | 3.13  |
| D                   | 0.380 |
| E                   | 5.00  |
| F (Normally Open)   | 11.13 |
| F (Normally Closed) | 16.05 |

## GENERAL

|                     |                                               |
|---------------------|-----------------------------------------------|
| Pressure Rating     | 6000 PSI                                      |
| Temperature Range   | -15°F to 400°F (-26°C to 204°C)               |
| Standard Soft Goods | [-G] Polyurethane® Packing and Viton® O-Rings |
| Cartridge Type      | Shutoff                                       |
| Connection Type     | Socketweld Pipe                               |
| Connection Size     | 3/8"                                          |
| Body Material       | 316/L Stainless Steel, ASTM A182, UNS S31603  |
| Bonnet Material     | 316/L Stainless Steel, ASTM A276, UNS S31603  |

## OPTIONS

|                      |                                                                                                           |
|----------------------|-----------------------------------------------------------------------------------------------------------|
| [-VC] Vacuum Service | Option to add additional softgoods for internal vacuum service.                                           |
| Optional Soft Goods  | [-B] Polyurethane® Packing and Buna-N O-Rings, [-C] Viton® Packing & O-Rings, [-D] EPDM Packing & O-Rings |