
Product Category
Product Line
Part Description

G2SGPS-06

G-Series® Shutoff Valve (G-S Series)

Globe Shutoff Valve with Socketweld Pipe Ends



## **DIMENSIONS**

Orifice	0.438
A (NPS)	0.675
В	3.13
D	0.380
E	3.50
F	5.06
G	2.59
J (max.)	0.44
K	1.53

## **DATA SHEET**

G2SGPS-06 11/05/2025 1:33 PM

## **GENERAL**

Pressure Rating	6000 PSI
Temperature Range	-15°F to 400°F (-26°C to 204°C)
Standard Soft Goods	[-G] Polyurethane® Packing and Viton® O-Rings
Cartridge Type	Shutoff
Connection Type	Socketweld Pipe
Connection Size	3/8"
Body Material	316/L Stainless Steel, ASTM A182, UNS S31603
Bonnet Material	316/L Stainless Steel, ASTM A276, UNS S31603

## **OPTIONS**

[-VC] Vacuum Service	Option to add additional softgoods for internal vacuum service.
Optional Soft Goods	[-B] Polyurethane® Packing and Buna-N O-Rings, [-C] Viton® Packing & O-Rings, [-D] EPDM Packing & O-Rings

https://www.cpvmfg.com 484.731.4010