
#### **DATA SHEET**

H859-02-02-SS316L 07/04/2025 4:45 AM



# Product Category

Part Description



### **DIMENSIONS**

| Α        | 0.130         |
|----------|---------------|
| B-THREAD | ,313" - 24UNF |
| C-HEX    | 0.5           |
| D        | 0.190         |
| E        | 1.38          |
| G-HEX    | 0.5           |

## **GENERAL**

| Pressure Rating   | 6000 PSI   |
|-------------------|--|
| Assembly Material | 316/L Stainless Steel, ASTM A276, UNS S31600/03    |
| O-Ring Material   | Viton® Fluorocarbon Type 1, Class 2 (90 durometer) |
| Connection 1 Type | Female Tube Socket                                 |
| Connection 1 Size | 1/80 Tube O.D. (-02)                               |
| Connection 2 Type | Male Straight Thread                               |
| Connection 2 Size | ,313" - 24UNF (-02)                                |

### https://www.cpvmfg.com 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the totabystem design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.



#### H859-02-02-SS316L

Tube to Male Straight Thread Union Assembly