



Product Category  
Product Line  
Part Description

G4SGPS-12-NO  
FloMaster® Actuated G-Series® Shutoff Valves (G-S Series)  
Globe Shutoff Actuated Valve, Socketweld Pipe Ends, Normally Open



## DIMENSIONS

|                     |       |
|---------------------|-------|
| Orifice             | 0.625 |
| A (NPS)             | 1.050 |
| B                   | 3.88  |
| D                   | 0.500 |
| E                   | 6.00  |
| F (Normally Open)   | 12.5  |
| F (Normally Closed) | 18.88 |

## GENERAL

|                     |   |
|---------------------|---|
| Pressure Rating     | 4500 PSI                                      |
| Temperature Range   | -15°F to 400°F (-26°C to 204°C)               |
| Standard Soft Goods | [-G] Polyurethane® Packing and Viton® O-Rings |
| Cartridge Type      | Shutoff                                       |

|                        |  |
|------------------------|--|
| <b>Connection Type</b> | Socketweld Pipe                              |
| <b>Connection Size</b> | 3/4"   |
| <b>Body Material</b>   | 316/L Stainless Steel, ASTM A182, UNS S31603 |
| <b>Bonnet Material</b> | 316/L Stainless Steel, ASTM A276, UNS S31603 |

## OPTIONS

|                             |   |
|-----------------------------|---|
| <b>[-VC] Vacuum Service</b> | Option to add additional softgoods for internal vacuum service.   |
| <b>Optional Soft Goods</b>  | [-B] Polyurethane® Packing and Buna-N O-Rings, [-C] Viton® Packing & O-Rings, [-D] EPDM Packing & O-Rings |

cpvmfg.com | 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.