



Product Category


Product Line

Part Description

G2NGPF-06

G-Series® Needle Valve (G-N Series)

Globe Needle Valve with Female Pipe Thread (NPT) Ends



DIMENSIONS

| | |
|----------|---------|
| Orifice | 0.438 |
| A-NPT : | 3/8"-18 |
| B | 3.13 |
| E | 3.50 |
| F | 5.06 |
| G | 2.59 |
| J (max.) | 0.44 |
| K | 1.53 |

GENERAL

| | |
|---------------------|---|
| Pressure Rating | 6000 PSI |
| Temperature Range | -15°F to 400°F (-26°C to 204°C) |
| Standard Soft Goods | [-G] Polyurethane® Packing and Viton® O-Rings |

| | |
|------------------------|--|
| Cartridge Type | Needle |
| Connection Type | Female Pipe Thread (NPT) |
| Connection Size | 3/8" |
| Body Material | 316/L Stainless Steel, ASTM A182, UNS S31603 |
| Bonnet Material | 316/L Stainless Steel, ASTM A276, UNS S31603 |

OPTIONS

| | |
|-----------------------------|---|
| [-VC] Vacuum Service | Option to add additional softgoods for internal vacuum service. |
| Optional Soft Goods | [-B] Polyurethane® Packing and Buna-N O-Rings, [-C] Viton® Packing & O-Rings, [-D] EPDM Packing & O-Rings |

cpvmfg.com | 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.