

Part Number:


1381-1-NC

Product Line:

FloMaster® Actuated O-SEAL® Shutoff Valve (1300 Series)

Part Description:

1/4" Angle Shutoff Actuated Valve, O-SEAL® Ends, Normally Closed



DIMENSIONS

Port Dia.:	0.31
B:	1.69
C :	1.5
CRN :	OC17716.2
D-THREAD :	1.188"-12UN
E:	4
F (Normally Closed):	13.44



GENERAL

Pressure Rating:	6000 PSI
Temperature Range:	-15°F to 400°F (-26°C to 204°C)
Standard Soft Goods:	[-G] Polyurethane® Packing and Viton® O-Rings
Cartridge Type:	Shutoff
Connection Type:	O-SEAL® Union Thread
Connection Size:	1/4"
Body Material:	Nickel Aluminum Bronze, ASTM B148, UNS C95800
Bonnet Material:	Nickel Aluminum Bronze, ASTM B150, UNS C63200
CRN:	0C17716.2

Options

[-VC] Vacuum Service:	Option to add additional softgoods for internal vacuum service.
[-P] Port & Vent Options:	[-PA] Port Above Seat (1/8" NPT), [-PB] Port Below Seat (1/8" NPT), '[-VA] Vent Above Seat (3/8"-24 SAE), [-VB] Vent Below Seat (3/8"-24 SAE),
Optional Soft Goods:	[-B] Polyurethane® Packing and Buna-N O-Rings, [-C] Viton® Packing & O-Rings, [-D] EPDM Packing & O-Rings